

PC SERIES CENTRIFUGAL PUMPS

Corrosion Resistant Centrifugal Pumps

PC Series

The compact, lightweight design of the PC Series pumps makes it ideal for cabinet installation, as well as skid mounting. They are corrosion resistant to provide you with reliable solutions for a variety of industrial, commercial, and agricultural applications.

The quality and performance you expect, along with industry best lead times and personalized service, only from Webtrol!



Features and Benefits

- Close coupled for a smooth transmission of power
- 316 stainless steel wear ring and impeller hub for long pump life
- Glass reinforced Noryl® pump case, motor bracket, and impeller
- Ease of Installation with the ability to rotate the discharge in 90° increments
- Suction pressures to 35 PSI (with 50 PSI boost)
- Mechanical seal type 6, 316 SS & Viton™

Performance

HP Range: .5 to 1.5 HP, 60Hz


Capacities to 65 GPM

Pressures to 50 PSI

Temperatures to 180 °F



Typical Services

- | | |
|---------------------------|----------------------------|
| • Deionized Systems | • Circulation Systems |
| • Reverse Osmosis Systems | • Pre-Filter Charge System |
| • Distribution Systems | • Condensation Systems |
| • Car Wash Systems | • Cooling Tower Systems |
| • Liquid Transfer Systems | |





PC SERIES GROUP CURVES

PCSeries



PC Series

PC SERIES GROUP CURVES






There when you need us most


PC SERIES GROUP CURVES

PC Series



PC Series

PC SERIES CENTRIFUGAL Dimensions



Construction & Design Features

.5 - 1.5 HP for Continuous Duty Operation

Model No.	A (Length)	HP
PC33R	8.51	.5
PC50R	8.51	.5
PC75R	9.36	.75
PC100R	9.36	1
PC150R	10.26	1.5

Motor - The end-mounting motor has no feet, and is supported by the motor bracket. An open drip-proof enclosure is standard with class B insulation.

CONSTRUCTION MATERIALS	
Part	Material
Pump Housing	Noryl®
Motor Bracket	Noryl®
Impeller (closed type)	Noryl®
Wear Ring	316 SS
Motor Shaft	303 SS
Mechanical Seal	Carbon/Ceramic
O-Rings	Viton™



There when you need us most

(800) 769-7867

8417 New Hampshire Ave. | St. Louis, MO 63123

Web: webtrol.com | **E-mail:** customerservice@webtrol.com | **Fax:** (314) 631-3738

WEBTROL is a Division of Weber Industries, Inc.